

125 TON

# Single Failure-Proof Trolley Rental



American Crane & Equipment Corporation has manufactured a 125-ton single failure proof NUREG 0554 compliant trolley for cask handling applications. The trolley features an adjustable trolley gauge to allow it to operate on crane bridges with spans between 14 feet and 17 feet. The trolley is electrically self-contained requiring only a 480 volt 3 phase supply. Operation of the trolley is via radio control to provide operator maximum flexibility.



LOAD TESTED IN AMERICAN CRANE'S TEST TOWER



KEY TECHNICAL DATA	
MAXIMUM CRITICAL LOAD (MCL):	125 Tons
DESIGN RATED LOAD (DRL):	125 Tons
DESIGN BASIS:	NUREG 0554
HOIST LIFT:	70'
HOIST SPEED:	4.5 FPM 5 Speed Stepped Critical Load (Programmable)
TROLLEY SPEED:	40 FPM 5 Speed Stepped (Programmable)
POWER SUPPLY:	460-3-60AC (125 AMPS)
MINIMUM TROLLEY GAUGE:	14'-0"
MINIMUM TROLLEY GAUGE:	17'-0"
TROLLEY HEIGHT:	5'-6"
AUXILIARY HOIST:	Available
TESTING:	Testing: Prior to Shipment

531 Old Swede Road · Douglassville, PA 19518 · 877.877.6778 · 610.385.6061  
info@AmericanCrane.com · www.AmericanCrane.com

