



**	A	17 1/4"
**	B	19 1/4"
	C	15 3/16"
	D	15 3/16"
	E	12 1/8"
	F	19 1/4"
	G	19"
	H	12 3/8"
	I	10 1/4"
	J	3 5/8"
	L	2"
#*	M	11 3/4"
#*	N	1 3/16"
^	S	13 1/2"
	T	7/16"

* TO WHEEL RUNNING SURFACE OF BEAM
 ** "B" APPLIES TO GEARED UNITS ONLY - FOR PLAIN UNITS DIM. "C" & "D" ARE MAX. 1/2 WIDTH
 # TO UNDER BEAM ROLLER - (CLOSEST POINT OF CONTACT)
 ^ FROM THE FACE OF WHEEL TO END OF AXLE
 CUSTOMER MUST TAKE INTO CONSIDERATION FLANGE WIDTH AND THICKNESS OF BEAM
 DIM. SHOWN ARE CORRECT FOR ANY "S" OR "W" BEAM, (FLAT TREAD WHEELS, NOT SHOWN, ARE SUPPLIED FOR "W" BEAM APPLICATIONS)

		20&24 TON LOW HEADROOM HOIST		DR. RLB	TR.	CK.	AP.
		CHESTER HOIST		SCALE NONE		DATE 6-19-00	
		LISBON, OHIO		REF. DWG. NO. 20ZLG4			
				Dwg. No. CD060			
MK.	REVISIONS	CK-DATE					