



**	A	13 1/2"
**	B	18 7/8"
	C	15 3/16"
	D	15 3/16"
	E	11 7/8"
	F	18 5/8"
	G	18 5/8"
	H	11 7/8"
	I	10 1/4"
	J	3"
	L	2"
#*	M	11 3/4"
#*	N	1 1/8"
^	S	13 1/2"
	T	7/16"

FOR MORE INFO CONTACT:
American Crane & Equipment Corp.
Authorized Distributor
Tel: 877-503-2972
Fax: 484-945-0430
Email: sales@americancrane.com
www.americancrane.com

- * TO WHEEL RUNNING SURFACE OF BEAM
 - ** "B" APPLIES TO GEARED UNITS ONLY - FOR PLAIN UNITS DIM. "C" & "D" ARE MAX. 1/2 WIDTH
 - # TO UNDER BEAM ROLLER - (CLOSEST POINT OF CONTACT)
 - ^ FROM THE FACE OF WHEEL TO END OF AXLE
- CUSTOMER MUST TAKE INTO CONSIDERATION FLANGE WIDTH AND THICKNESS OF BEAM

DIM. SHOWN ARE CORRECT FOR ANY "S" OR "W" BEAM, (FLAT TREAD WHEELS, NOT SHOWN, ARE SUPPLIED FOR "W" BEAM APPLICATIONS)

MK.	REVISIONS	CK-DATE

16 TON LOW HEADROOM HOIST

CHESTER HOIST
LISBON, OHIO

DR. RLB	TR.	CK.	AP.
SCALE NONE		DATE 6-19-00	
REF. DWG. NO.	16ZLHR4 UPDATED		
Dwg. No. CD059			