



**	A	17 1/4"
**	B	19 1/4"
	C	15 3/16"
	D	15 3/16"
	E	12 1/8"
	F	19 1/4"
	G	19"
	H	12 3/8"
	I	10 1/4"
	J	3 5/8"
	L	2"
#*	M	11 3/4"
#*	N	1 3/16"
^	S	13 1/2"
	T	7/16"

**FOR MORE INFO CONTACT:**  
**American Crane & Equipment Corp.**  
**Authorized Distributor**  
**Tel: 877-503-2972**  
**Fax: 484-945-0430**  
**Email: sales@americancrane.com**  
**www.americancrane.com**

\* TO WHEEL RUNNING SURFACE OF BEAM  
 \*\* "B" APPLIES TO GEARED UNITS ONLY - FOR PLAIN UNITS DIM. "C" & "D" ARE MAX. 1/2 WIDTH  
 # TO UNDER BEAM ROLLER - (CLOSEST POINT OF CONTACT)  
 ^ FROM THE FACE OF WHEEL TO END OF AXLE  
 CUSTOMER MUST TAKE INTO CONSIDERATION FLANGE WIDTH AND THICKNESS OF BEAM  
 DIM. SHOWN ARE CORRECT FOR ANY "S" OR "W" BEAM, (FLAT TREAD WHEELS, NOT SHOWN, ARE SUPPLIED FOR "W" BEAM APPLICATIONS)

20&24 TON LOW HEADROOM HOIST

**CHESTER HOIST**  
 LISBON, OHIO

DR. RLB	TR.	CK.	AP.
SCALE NONE		DATE 6-19-00	
REF. DWG. NO. 20ZLG4			
Dwg. No. CD060			

MK.	REVISIONS	CK-DATE
-----	-----------	---------